



Technical Specifications

Basis weight	130 g/m ²
Thickness	9.5 mil
ISO brightness	95%
Opacity	97%
Gloss at 60°	2.8
Hot lamination	Yes
Base material	Tyvek® Spun-bonded Polyethylene
Surface finish	Matte
Core size	2"
Spindle	2" standard

Operating Specifications

Required temperature for optimum performance	59° - 77° F 15° - 25° C
Required humidity for optimum performance	40% - 60% RH

(Note: High humidity will prolong the drying time for lamination purposes.)

Driver Settings

Select Tyvek® as the media type setting. If Tyvek® is not available, select Synthetic Paper setting.

Ordering Specifications (Individual Boxes)

Product Code	Product	UPC
S041494	24" x 60"	0-10343-83625-9
S041495	36" x 60"	0-10343-83626-6
S041496	44" x 60"	0-10343-83627-3

Packaging Specifications (Individual Boxes)

Product Code	Dimensions (L x W x H)	Weight
S041494	25" x 4.6" x 4.6"	5.5 lbs
S041495	37" x 4.6" x 4.6"	7.0 lbs
S041496	45" x 4.6" x 4.6"	9.0 lbs

MSRP* (Per Unit)

Product Code	Product	Cost
S041494	24" x 60"	\$179
S041495	36" x 60"	\$269
S041496	44" x 60"	\$329

*Actual prices may vary.

YOU'VE GOT TO SEE IT IN  COLOR.™

www.epson.com

Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America
6303 Blue Lagoon Drive, Miami, FL 33126

Specifications are subject to change without notice. EPSON and EPSON Stylus are registered trademarks of Seiko Epson Corporation. EPSON Archival is a trademark of Epson America, Inc. All other products and brand names are registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.
Copyright © 2001 Epson America, Inc. CPD-10286 5K 4/01 CL

Printed on Recycled Paper 