



hp banners with Tyvek®



data sheet

Create brilliant, durable banners that last indoors and outdoors. This tough printing material resists tears, fading and water damage. Create waterfast and lightfast prints that last for up to three months outdoors without lamination and are easy to hang, add grommets and stitch.

target customers

- print service providers
- sign shops
- screen printers
- retail

applications

- durable indoor and outdoor banners
- trade show graphics
- window displays
- murals
- backdrops and theatrical sets

user needs

- lightfast, water-resistant
- no lamination required
- grommitable, sewable and drapable

printer & ink compatibility

hp designjet 5000 series printers	hp 83 UV ink supplies
hp designjet 3000CP series	hp designjet cp ink systems UV
hp designjet 2000CP series	hp designjet cp ink systems UV
hp designjet 1000 series	hp 80 ink supplies
hp designjet 800/500 series	hp 10 black ink, hp 82 CMY ink, hp 11 CMYK printheads

mounting and laminating

mounting	yes
laminating	no
grommeting	yes

product specifications

weight.....	140 g/m ²
thickness/caliper.....	10 mil / 254µ
smoothness.....	359 SU
whiteness	130 per CIE Ganz 82 test method
brightness	90 per TAPPI T-452 test method
opacity.....	>90 per TAPPI T-425 test method
country of origin	United States

performance specifications

storage temperature.....	15°– 35°C (59°–95°F)
storage humidity.....	20%-60% RH
lightfastness	Delta E < 10 (3 months outdoors)
waterfastness.....	Delta OD<0.10
dry time	7 minutes
shelf life.....	1 year minimum

ordering information

C6787A	36 in. x 50 ft. (914 x 15,2 m)
C6789A	54 in. x 50 ft. (1372 mm x 15,2 m)

Tyvek® is a Dupont registered trademark.

For more information about HP Premium Printing Material, visit www.designjet.hp.com/supplies